

Remote Controllers

Our air conditioning systems are supported by a multitude of remote controllers. Each remote controller type, whilst being able to support the general control and monitoring functions for a group of indoor units, can also offer other unique operational features.



PAC-YT51CRB



PAC-SE51CRA



BS-51COV-B



PS-51COV-B



PB-51COV-B



PAR-(W)21MAA



PAR-F27MEA



PAR-FL32MA

Technical Information

Remote Controllers

FUNCTION	DESCRIPTION	PAC-YT51CRB		PAC-SE51CRA		PAR-(W)21MAA		PAR-F27MEA		PAR-FL32MA	
		Operation	Display	Operation	Display	Operation	Display	Operation	Display	Operation	Display
ON/OFF	Run and Stop operation for a single group	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
MODE SELECTION	Switches between Cool/Dry/Auto/Fan/Heat. Operation mode will vary depending on the indoor unit. Auto mode is available with only R2 and WR2 systems		✓		✓	✓	✓	✓	✓	✓	✓
TEMPERATURE SETTING	Sets the groups temperature control. Cool/Dry: 19-30°C Heat: 17-28°C Auto: 19-28°C	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
FAN SPEED SETTING	4 speed - Lo-Mi1-Mi2-Hi 2 speed - Lo-Hi	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
SETPOINT LIMIT	Limit the setpoint range				✓	✓	✓	✓	✓		
AIRFLOW DIRECTION	Air Flow angles: 100°-80°-60°-40° and auto swing					✓	✓	✓	✓	✓	✓
INDEPENDENT VANE CONTROL	Only available with PLA-RP-BA, PLFY-P-VBM-E and PLFY-P-VCM-E					✓	✓				
TIMER OPERATION	ON/OFF time can be set.					Weekly	Weekly	Daily	Daily	Daily	Daily
PERMIT / PROHIBIT FUNCTION	Run/Stop, Temperature Setting, Mode Selection and Filter Reset functions can be prohibited via a higher level system controller		✓		✓	✓		✓			✓
INDOOR RETURN AIR TEMPERATURE	Measures the intake temperature of the master unit within the group					✓		✓			
ERROR INDICATION	Displays a 4 digit code and the affected unit address		✓		✓	✓		✓			
TEST RUN FUNCTION	Allows each unit within the group to operate in test mode		✓		✓	✓	✓	✓	✓	✓	✓
VENTILATION INTERLOCK	Allows the group to be interlocked with a heat recovery Lossnay unit					✓	✓	✓	✓		
OPTIONAL COVER	Brushed Stainless Steel Polished Stainless Steel Polished Brass		✓ ✓ ✓		✓ ✓ ✓						
CONTACT NUMBER UNDER FAULT CONDITIONS	Displays under fault condition, the fault code of the unit with its address and the contact number to call						✓				
MULTIPLE LANGUAGES	English, Italian, Spanish, French, German, Russian, Chinese and Japanese					✓	✓				
CLOCK DISPLAY	Displays time					✓					
BUTTON LOCK	Able to lock all controller buttons, or all controller buttons except On/Off					✓	✓	✓	✓		
EASY MAINTENANCE WITH MR SLIM	Able to monitor information about the compressor (running current, running time, On/Off time). Also able to monitor sensors: h-exh, outdoor outlet, outdoor temp, indoor inlet, indoor h-exh and filter use number of hours					✓	✓				
RUN / STANDBY WITH MR SLIM	Able to switch over two systems every week. If one fails, the other system starts. If the temperature is too high, the two systems start.					✓	✓				
COMPATIBILITY	Compatible with:	Mr Slim or M Series (via MAC-397IF)		City Multi		Mr Slim or M Series (via MAC-397IF)		City Multi		City Multi, Mr Slim or M Series (via MAC-397IF)	
DIMENSIONS - mm (WxDxH)		120x41x70		120x41x70		130x19x120		130x19x120		157x18x57	

NOTE: For PAR-W21MAA extra functionality, please see the relevant technical manual.